







Photo non contractuelle.

PHD200

 CARACTERISTIQUES	 SPECIFICATIONS	 SPEZIFIKATIONEN	 CARACTERÍSTICAS	
Constructeur	Manufacturer	Konstrukteur	Fabricante	BLISS
Capacité	Capacity	Nennkraft	Fuerza	2000 kN
Course	Stoke	Hub	Carrera	400 mm
Ouverture mini	Min. opening	Min. Öffnung	Apertura mínima	240 mm
Dimensions table	Bolster dimensions	Tischfläche	Mesa	1250 × 1000 mm
Dimensions coulisseau	Ram dimensions	Stößelfläche	Base corredera	1000 × 800 mm
Hauteur table / sol	Bolster/ floor height	Höhe Tisch / Bode	Altura mesa / suelo	900 mm
Puissance moteur principal	Main motor power	Nennleistung Hauptmotor	Potencia motor principal	37 kW
Vitesse d'approche rapide	Fast approach speed	Leerhubgeschwindigkeit	Velocidad de acercamiento rápida	200 mm/sec
Vitesse de travail à force max	Working speed at max capacity	Arbeitsgeschwindigkeit	Velocidad de trabajo con fuerza máxima	13,6 mm/sec
Force au retour	Return capacity	Rücklaufkraft	Fuerza en el retorno	270 kN
Coussin	Cushion	Kisse	Almohadilla	
Force du coussin	Cushion capacity	Leistung Kissen	Fuerza de la almohadilla	600 kN
Course du coussin	Cushion stroke	Hub Kissen	Carrera de la almohadilla	150 mm